

K-Flex ST Frigo

Endlosschlauch

Preise gültig ab 1. April 2012 exkl. MwSt.
Änderungen vorbehalten



K-Flex ST Frigo Endlosschlauch mit gleichbleibender Dämmstärke

Kartongrösse 51x51x21cm

Nummer	Rohr Ø Zoll	Rohr Ø mm	Stärke mm	Länge m	CHF/Kt
B122660	Cu 1/4"	6	6	50	102.80
B122690	Cu 5/16"	8	6	48	102.80
B122720	Cu 3/8"	10	6	46	102.80
B122750	Cu 1/2"	12	6	40	102.80
B122780	Cu 5/8"	15	6	38	102.80
B122810	Cu 3/4"	18	6	30	102.80
B122840	Cu 7/8"	22	6	23	102.80
B122870	Cu 1 1/8"	28	6	20	102.80
B122670	Cu 1/4"	6	9	40	102.80
B122700	Cu 5/16"	8	9	37	102.80
B122730	Cu 3/8"	10	9	34	102.80
B122760	Cu 1/2"	12	9	31	102.80
B122790	Cu 5/8"	15	9	27	102.80
B122820	Cu 3/4"	18	9	23	102.80
B122850	Cu 7/8"	22	9	19	102.80
B122880	Cu 1 1/8"	28	9	14	102.80
B122680	Cu 1/4"	6	13	26	102.80
B122710	Cu 5/16"	8	13	26	102.80
B122740	Cu 3/8"	10	13	23	102.80
B122770	Cu 1/2"	12	13	18	102.80
B122800	Cu 5/8"	15	13	17	102.80
B122830	Cu 3/4"	18	13	15	102.80
B122860	Cu 7/8"	22	13	14	102.80
B122890	Cu 1 1/8"	28	13	10	102.80

Technische Daten

Farbe schwarz

Wasserdampfsperwert > 7000 μ

Brandkennziffer 5.2

Abschottungen / Durchführungen BZ 13533 und 13534

Einsatztemperatur -20°C bis +105°C

Wärmeleitfähigkeit 0°C = 0.036W/mK

Korrosionsrisiko niedrig DIN 1988/7