


K-FLEX


**ISOGLOBAL ROHRTRÄGER IF MIT
SCHNELLVERSCHLUSSROHRSCHELLE**

Art.Nr.	Rohr Ø mm	DSD mm	aussen Ø mm	Breite mm	Stk/Krt	CHF/Stk
B211280	10-12	13	38	45	50	11.75
B211290	15-18	13	44	45	50	12.10
B211300	22-25	13	51	55	50	12.60
B211310	28-30	13	56	55	50	15.65
B211320	34-38	13	64	55	50	16.70
B211330	42-45	13	71	55	50	17.50
B211340	48	13	74	55	50	18.80
B211350	54-57	13	83	65	25	19.40
B211360	60-64	13	90	65	25	22.00
B211370	76-80	13	106	75	25	26.45
B211380	89	13	115	75	15	36.65
B211400	10-12	19	50	55	50	14.35
B211410	15-18	19	56	55	50	15.05
B211420	22-25	19	63	55	50	15.65
B211430	28-30	19	68	55	50	19.40
B211440	34-38	19	76	65	50	22.10
B211450	42-45	19	83	65	25	23.25
B211460	48	19	86	65	25	25.40
B211470	54-57	19	95	65	25	26.55
B211480	60-64	19	102	65	25	30.10
B211490	76-80	19	118	75	15	37.75
B211500	89	19	127	75	15	48.20
B211580	10-12	32	50	65	50	22.15
B211590	15-18	32	82	65	50	22.20
B211600	22-25	32	89	75	50	26.45
B211610	28-30	32	94	75	25	28.45
B211620	34-38	32	102	75	25	33.85
B211630	42-45	32	109	75	25	37.05
B211650	54-57	32	121	75	12	42.20

Technische Daten (Änderungen vorbehalten)


Wärmeleitfähigkeit Dämmstärke: 0°C = 0.033W/mK

Wasserdampfsperrwert Dämmstärke: 10000 µ

Brandverhalten: E

Einsatztemperatur: -50°C bis +110°C

K-FLEX


**ISOGLOBAL ROHRTRÄGER IF MIT
SCHRAUBENVERSCHLUSSROHRSCHELLE**

Art.Nr.	Rohr Ø mm	DSD mm	aussen Ø mm	Breite mm	Stk/Krt	CHF/Stk
B211810	102-108	13	134	100	15	41.00
B211390	110-114	13	140	115	8	52.55
B211820	125	13	151	115	8	53.60
B211830	133-140	13	166	115	6	55.50
B211840	160	13	186	115	6	63.95
B211850	165-168	13	194	125	2	69.00
B211860	102-108	19	146	100	15	55.00
B211510	114	19	152	100	8	68.65
B211520	125	19	163	115	6	69.45
B211530	133-140	19	178	115	4	74.05
B211540	159-160	19	198	115	2	78.85
B211550	165-168	19	206	125	2	88.50
B211560	216-219	19	257	125	2	137.90
B211570	267-273	19	311	125	2	173.15
B211870	324	19	362	150	1	230.05
B211880	356	19	394	200	1	245.90
B211890	406	19	444	200	1	270.00
B211640	48	32	112	75	25	38.10
B211660	60-64	32	128	85	12	49.25
B211670	76-80	32	144	85	12	67.70
B211680	89	32	153	100	8	76.85
B211690	110-114	32	178	100	6	121.65
B211700	125	32	189	125	2	131.30
B211710	133-140	32	204	125	2	138.00
B211720	160	32	224	140	2	168.95
B211730	168	32	232	140	2	173.60
B211740	219	32	283	140	2	234.50

Technische Daten (Änderungen vorbehalten)

Wärmeleitfähigkeit Dämmstärke: 0°C = 0.033W/mK

Wasserdampfsperwert Dämmstärke: 10000 µ

Brandverhalten: E

Einsatztemperatur: -50°C bis +110°C

K-FLEX


GEWINDESTANGE

Art.Nr.	Format mm	Stk/Krt	CHF/Stk
B211900	8x1000	50	2.40
B211910	10x1000	25	3.60
B211920	12x1000	20	5.15
B211930	16x1000	10	10.00


GRUNDPLATTEN

Art.Nr.	Format mm	Stk/Krt	CHF/Stk
B211940	80x30	100	1.60
B211950	120x40	50	3.40
B211960	120x40	50	3.65